

DRIVEN BY AIR.



Preset Tyre Inflator

ACCURA Compact

Safe, simple and space-saving preset inflation



The ACCURA Compact is PCL's most simple electronic tyre inflator to date, and offers a space-saving solution for car dealerships, garages, car fleets, and OEMs, where ease of use and accuracy are key.

The contemporary, user friendly design with touch screen technology, means that customer can pre-set the required pressure and place the connector on the tyre, leaving the in-built auto-start function to do the rest. The ACCURA Compact is robust yet

attractive, featuring the new PCL branding. Durable and easy to install it offers extremely precise measurement with tolerances well above the industry standard EC 86/217.

In short, the ACCURA Compact provides straight-forward, cost-effective inflation while achieving the benefits of extended tyre life, increased fuel efficiency and increased safety for the vehicle.

A HORNGROUP COMPANY

Key benefits

For the Operator:

- Consistent cost effective supply of high levels of safe air inflation services
- Low life time costs – long product life with robust design and proven electronics
- Low and simple maintenance
- Simplicity
- Guaranteed accuracy with individual testing

For the Tyre User/Fleet Manager

Accurate tyre pressures give:

- Extended tyre life
- Increased fuel economy
- Increased safety and reduced tyre-related incidents

Key features

- Electronic pressure preset
- Auto-start inflation
- Clear display for easy customer usage
- Default to safe-setting
- Space-saving and lightweight design
- Robust high reliability engineering plastic housing
- Ceramic sensor – Accuracy to ±0.5% of full scale reading
- Attractive and durable membrane
- 230 V, 100 V/120 V and 12 V versions
- Can inflate accurately with hoses up to 50 m in length

Specifications

Dimensions

H x W x D: 255 mm x 220 mm x 100 mm
(10.04" x 8.66" x 3.94")
Weight: 3.2 kg (7.06 lbs)

Environmental

Temperature range:
Operating: -20 °C to 70 °C
Storage: -30 °C to 80 °C
Humidity Range: Up to 95% RH non-condensing

Electrical Interface

Voltage:
Nominal 230 Vac 100/120 Vac 12 Vdc
Min 175 Vac 75 Vac 10 Vdc
Max 265 Vac 140 Vac 16 Vdc
Current:
Typical 0.1 A 0.1 A 0.1 A
Maximum 0.7 A 0.7 A 0.7 A

Pressure Measurement

Accuracy to ±0.5% of full scale reading
Reading Accuracy: 1 PSI / 0.1 bar / 5 kPa / 0.1 kg/cm²
Max Inlet Pressure: 232 PSI / 16 bar / 1600 kPa / 16.3 kg/cm²
Inflation Range: 145 PSI / 10 bar / 999 kPa / 10.2 kg/cm²

Inflation Speeds

Inflation flow: 400l/min @ 10bar supply

Compliance

Complies to: EC Directive 86/217/EEC,
BS EN 12645:1999 & CE

Operational specification

- IP Rating – IP66
- Zero drift
- 30 mm backlit transfective LCD
- Auto-start inflation
- Hose standard 7.6 m with twin hold on connector
- Safe rate of change algorithm
- Audible and visual end of cycle signals
- Default to safe setting
- Coin/Token and compressor interfaces

Optional Features

- Hose length and type
- Connector type



08/2013 subject to technical changes

PCL is the world leader in the design and manufacture of tyre inflation and compressed air products.

Pneumatic Components Limited
Holbrook Rise
Holbrook Industrial Estate
Sheffield S20 3GE

T +44 (0)114 248 2712
F +44 (0)114 247 8342
info@pclairtechnology.com
www.pclairtechnology.com